

THE GATOR TX.

ALSO INCLUDES:

HIGH-BACK BUCKET SEATS

12-VOLT DC OUTLET

4-WHEEL HYDRAULIC
DISK BRAKES

REAR RECEIVER HITCH

Top-of-the-line two-wheel drive.

Step up to the enhanced Gator TX from the TS and you'll appreciate the steep horsepower increase under the hood and the Deluxe Cargo Box in the rear. Whether you load it up or leave it empty, the TX delivers a well-cushioned ride with a specially tuned four-wheel suspension. Get one. And get the job done.



More power under the hood delivers more torque, excellent low-end lugging power and faster acceleration everywhere you go.



With a four-wheel suspension with coil over shock, triple-rate adjustable springs and a four-inch longer wheelbase, the TX rides smoother than ever before.



Deluxe Cargo Box includes 16.4 cubic feet of capacity, pick-up style tailgate, 20 tie-down points, a gas-assist shock for easier lifting and dumping, and the ability to convert to a flat-bed mode in minutes by removing the composite side panels and tailgate. You can also order a factory-installed spray-in bedliner.

SPECIFICATIONS	Gator TX 4x2
Engine and Electrical	
Type	19 hp* (14.2 kW), Air-cooled, overhead-valve 2-cylinder, 4-cycle gas
Displacement	675 cc (41.2 cu. in.)
RPM, idle 1 fast (no load)	1125 +/-75 / 3850 +/-75
Maximum torque	37.0 lb.-ft. @ 2400 rpm
Transmission	
Type	Continuously variable transmission (CVT)
Speed	0-20 mph (0-32 kph) forward, 0-19.4 mph (0-31.2 km/h) reverse
Differential Lock	Standard, hand-operated
Transaxle	Fully enclosed, oil bath
Gear Selection	Forward, neutral, reverse
Suspension and Steering	
Front	Independent spring over shock, single A-arm
Total travel	5 in. (127 mm)
Rear	Semi-independent Adjustable Coil over Shock
Total travel	3 in. (76.2 mm)
Steering	Rack and pinion
Turning radius	12 ft. (3.65 m)
Brakes	
Park brake	All-wheel hydraulic disc
Rear	Rear mechanical disc, hand operated
Tires	
Front	Two 22x9 50-10, 4 PR
Rear	Two 24x10 50-10 HPAP; 24x12-10 Turf/ Hard Surface & HPAT
Fuel System	
Capacity	5 U.S. gal (18.9 L)
Cargo Box	
Material	Polypropylene side panels and tailgate, steel floor and load guard
Electric lift	Optional
Capacity	600 lb. (272 kg)
Depth	12 in. (304.8 mm)
Length	45 in. (1143 mm)
Volume	16.4 cu.ft. (0.46 cu. m)
Width	52 in. (1320 mm) inside
Height above ground	30 in. (762 mm)
Tailgate	Hinged at bottom, removable / side panels are removable
Weight, lb. (incl fuel, fluids)	1120 lb. (508 kg)
Seating type	2, Professional High Back, tilt forward
Seat adjustment	Optional, driver's side
Dimensions	
Height	43.6 in. (1108 mm)
Width	60 in. (1525 mm)
Length with/without bumper	112.1 in. (2847 mm)/109.6 in. (2788 mm)
Ground clearance, under foot platform	10.6 in. (270 mm)
under transaxle	5.7 in. (145 mm)
Wheelbase	72.5 in. (1841 mm)
Payload/towing capacity	1000 lb. (454 kg)
Ground Pressure	6.2 psi (0.44 kg/cm ²) front, 11.6 psi (82 kg/cm ²) rear
(With 200 lb. operator only)	

* Engine hp is provided by engine mfr. for comparison purposes only. Actual operating hp will be less.

POPULAR OPTIONS: Heavy-duty bumper and brush guard • Deluxe cab • Horn/light kits • Cargo box power lift kit • Blades/Sprayers • Front receiver hitch