

410 Features

410 Turf Tender Pull Type

Pull Unit Requirements:

Requires 3-7 GPM. Oil flow without optional power unit

Overall Dimensions:

Overall Length 144 inches
Overall Width 60 inches
Height 50 inches
Weight: 920 Lb.
Weight 1240 Lb. (with optional power unit)

Hopper:

Capacity 23 cu Ft. (.65 m³) level, 27 cu Ft. (.76m³) heaped
Trackless 18 inch PVC Belt (crescent style)
Rear Door adjusted from 0-7 inches.
Powder Coat Paint
Hopper Length 76 inches

Frame:

Welded Heavy Duty A-Frame Construction.
Jack Stand

Tires:

2 Ultra Trac Turf Tires. 26.5x14x12

Options:

Controls:

Electric Over Hydraulic Machine (controls belt and spinner speed from the vehicle mounted control panel with speed gauges)
Manual Hydraulic Machine (valves on the side of the machine to control the belt and spinner speed) with vehicle mounted on/off switches

Dual Spinner System:

2 Throw discs (24 inch diameter, 6 adjustable paddles per disc.)
Quick Change
2 hydraulic motors, 1 per spinner-disc
Spreading width 12-40 foot variable
Spreading application (extremely fine to very heavy)
Capable of spreading a large variety of materials

Optional Spinners:

Black spinners (Fertilizer)
Green Spinners (Grass seed)

Optional Power Unit:

Honda 11hp Engine
Electric Start
1.72 US Gal. Fuel tank.
Max. Pressure 2500 psi
Max. Flow 7.26 gpm
Reservoir size 6.75 gal.

Optional Rear Conveyor

410 Turf Tender Mounted

Models: Mounted

Mounts on John Deere ProGator™ or Toro Workman™

Requirements:

John Deere™ PTO Hydraulic kit required on John Deere ProGator™.
DAKOTA Auxiliary hydraulic kit required on Toro Workman™ on models older then 2001, 2002 and newer requires Toro High Flow hydraulics

Overall Dimensions:

Overall length 103 inches
Overall Width 60 inches
Height 54 inches
Weight 780 lbs. with sub-frame

Hopper:

Capacity 23 cu. Ft. (.65m³) level 27 cu Ft. (.76m³) heaped (Note: Do not exceed recommended vehicle load rating for John Deere ProGator™ or Toro Workman™)
Trackless 18 inch PVC Belt (crescent style)
Rear Door adjusted from 0-7 inches.
Powder Coat Paint
Hopper Length 76 inches

Frame:

Welded Heavy duty sub-frame
Mounts using existing cylinder and box mount

Options:

Controls:

Electric Over Hydraulic Machine (controls belt and spinner speed from the vehicle mounted control panel with speed gauges)
Manual Hydraulic Machine (valves on the side of the machine to control the belt and spinner speed) with vehicle mounted on/off switches

Dual Spinner System:

2 Throw discs (24 inch diameter, 6 adjustable paddles per disc.)
Quick Change
2 hydraulic motors, 1 per spinner-disc.
Spreading width 12-40 foot variable.
Spreading Application is adjustable (extremely fine to very heavy)
Capable of spreading a large variety of materials.

Optional Spinners:

Black Spinners (Fertilizer)
Green Spinners (Grass Seed)

Optional Parking Stand:

Easy on/off using 4 legs
Rear legs are jack stands

Optional Rear Conveyor



Optional parking stands for easy removal and storage of mounted units.





Improved wiper system prevents leaking.



Electric controls with LED readouts and a key start for engine models.

Optional rear conveyor. Fits all 410 models.



410

Pull-types available with 11 horsepower Honda engine.



Available 2 valve manual controls.



Fully adjustable spinners allow even spread for many different materials.